

Hydrating Lip Cream

C-1009-01

DESCRIPTION

This lip color delivers a luxurious satin rich color to the lips, while enhancing the hydration.

ADVANTAGES

MEADOWESTOLIDE® provides moisturizing benefits and a luxurious feel.

BENTONE GEL® VS-5 V gives stable thixotropic viscosity control, while suspending the pigments and enabling controlled alignment of special effect pigments.

Phase	Ingredient	Supplier	%w/w
A	C14-22 Alkane (Lilac)	Sonneborn	20.00
	Dimethicone (and) Dimethicone/Vinyl Dimethicone Crosspolymer (Caresil CX G-1104)	Nusil	16.00
	Cyclopentasiloxane (and) Distearidimonium Hectorite (and) Alcohol (BENTONE GEL® VS-5 V)	Elementis	15.00
	Dimethicone (KF-96A-6cs)	Shin Etsu	10.25
	Tricaprylin (Dermafeel MCT)	Evonik	10.00
	Hydrogenated Polycyclpentadiene (and) Polyethylene (and) Copernicia Cerifera (Carnauba) Wax (and) Tocopherol (Koboguard HRPC)	Kobo	7.00
	Iron Oxides (and) Isononyl Isononanoate (and) Isopropyl Myristate (and) Stearalkonium Hectorite (and) Polyhydroxystearic Acid (and) Propylene Carbonate (INBP50R33A)	Kobo	4.00
	Nylon-12 (SP-10)	Kobo	4.00
	Meadowfoam Estolide (MEADOWESTOLIDE®)	Elementis	3.00
	Red 33 Lake (and) Isononyl Isononanoate (and) Isopropyl Myristate (and) Stearalkonium Hectorite (and) Polyhydroxystearic Acid (and) Propylene Carbonate (INBP50R33A)	Kobo	3.00
	Polyethylene (and) Microcrystalline Wax (PM Wax 82)	Kobo	2.75
	Ozokerite Wax		2.50
	Cera Alba (Yellow Beeswax)	Stahl & Pitsch	1.75
	Caprylyl Glycol (and) Caprylylhydroxamic Acid (and) Glycerin (Spectrastat)	Inolex	0.75

Procedure:

1. Combine Phase A and heat to 75-80°C.
2. Mix using propeller mixer until uniform.
3. Begin cooling.
4. At 30°C pour off into desired containers and allow to cool.

Reference: 03356-4

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Registered trademark of Elementis Specialties, Inc.

V02 April 2018

North America

Elementis
469 Old Trenton Road
East Windsor, NJ 08512, USA
Tel.: +1 609 443 2500
Fax: +1 609 443 2422

Europe

Elementis UK Ltd.
c/o Elementis GmbH
Stolberger Strasse 370
50933 Cologne, Germany
Tel.: +49 221 2923 2066
Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd.
99, Lianyang Road
Songjiang Industrial Zone
Shanghai, China 201613
Tel.: +86 21 5774 0348
Fax: +86 21 5774 3563