

Lustrous Conditioning Lipstick

C-1012-01

DESCRIP	TIO	N
----------------	-----	---

This glossy lip color has been enriched with MEADOWESTOLIDE® and FANCOR® Abyssinian Oil to moisturize and soften the lips while delivering a striking color.

ADVANTAGES

FANCOR® Abyssinian Oil provides a natural lustre and provides excellent pigment wetting. It delivers an elegant cushioning skin feel.

MEADOWESTOLIDE® provides moisturization and contributes to a luxurious skin feel.

BENTONE GEL® PTIS V improves the suspension of the pigments and enhances stability of the formulation during cool down and helps to eliminate sweating.

SPECIFICATIONS

Appearance: Red lipstick

Phase	Ingredient	Supplier	%w/w
Α	Crambe Abyssinica Seed Oil (FANCOR® Abyssinian Seed Oil)	Elementis	25.00
	Red 7 Lake	Sun Chemical	3.50
	Titanium Dioxide	Sensient	2.25
	Yellow 5 Lake (Unipure Yellow LC125)	Sensient	1.25
В	Limnanthes Alba (Meadowfoam) Seed Oil (FANCOR® Meadowfoam Seed Oil)	Elementis	22.85
	Pentaerythrityl Tetraisostearate (and) Disteardimonium hectorite (and) Propylene Carbonate (BENTONE GEL ® PTIS V)	Elementis	10.00
	Pentaerythrityl Tetraisostearate (Crodamol PTIS)	Croda	7.75
	Euphorbia Cerifera (Candelilla) Wax	Koster Keunen	6.30
	Talc (J-68-BC)	US Cosmetics	6.00
	Microcrystalline Wax (Multiwax 180-W)	Sonneborn	5.60
	Copernicia Cerifera (Carnauba) Wax	Koster Keunen	4.00
	Meadowfoam Estolide (MEADOWESTOLIDE ®)	Elementis	3.00
	Beeswax	Strahl & Pitsch	2.00
	Phenoxyethanol (and) Ethylhexylglycerin (Euxyl PE9010)	Schulke	0.50

Procedure:

- Blend Phase A together until completely wetted out and dispersed with no agglomerations.
- 2. Heat Phase B to 85°C and mix until homogeneous.
- 3. At 85°C combine pigment premix Phase A and Phase B until uniform.
- 4. Cool to 65°C and fill into molds or appropriate packaging.

Reference: BY-3222-01A

NOTE: The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchasers will be subject to a separate agreement which will not incorporate this document.

© Copyright 2018, Elementis Specialties, Inc. All rights reserved. Copying and/or downloading of this document or information therein for republication is not allowed unless prior written agreement is obtained from Elementis Specialties, Inc.

® Registered trademark of Elementis Specialties, Inc.

V02 April 2018

North America

Elementis 469 Old Trenton Road East Windsor, NJ 08512, USA Tel.: +1 609 443 2500 Fax: +1 609 443 2422

Europe

Elementis UK Ltd. c/o Elementis GmbH Stolberger Strasse 370 50933 Cologne, Germany Tel.: +49 221 2923 2066 Fax: +49 221 2923 2011

Asia

Deuchem (Shanghai) Chemical Co., Ltd. 99, Lianyang Road Songjiang Industrial Zone Shanghai, China 201613 Tel.: +86 21 5774 0348 Fax: +86 21 5774 3563