
Aristoflex BLV

Polymeric sulphonic acid,;partially neutralized

Global Product Specification

Country of Origin:
Tarragona / Spain

Item	Specification	Unit	Method
Appearance	white powder		visual
Solid content	min. 92.0	%	Clariant
Water content Karl-Fischer	max. 7.0	%	DIN 51777
pH value (1% solution)	4.0 - 6.0		DIN EN 1262
Viscosity 1% Soln. Spindle 6	14000 - 29000	mPas	DIN EN ISO 2555
Viscosity 0.5% Soln. Spindle 4	2500 - 7500	mPas	DIN EN ISO 2555

Remarks: Material is sieved - Mesh size 2mm

Water content determined on the date of batch release. Product is hygroscopic and may increase water content during storage, particularly if not stored correctly. Chemical stability of the polymer and its performance in applications are not affected by increased water content.

Product Code: 234471

Version: 2
Date of Issue: 18.05.2021

This product specification would cease to be binding if the customer has not purchased the product during the preceding 12 months. This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial rights must be observed. ISO-, EN- and DIN-Standards are published by: Beuth-Verlag, Burggrafenstr. 6, D-10787 Berlin, Germany. They are also available from the National Standard authority of each country. DGF-Standards are published by: Wissenschaftliche Verlagsgesellschaft mbH, Birkenwald Str. 44, D-70191 Stuttgart, Germany. This Product Specification is not signed. If you have any questions, please contact the local Clariant Office. Please visit our website <http://www.clariant.com>.

This document does not require a signature.